


Datasheet Aluminum Combi joist

Dimension : 40 x 60 x 4000 mm
Alloy : EN AW 6060 T 66, for marine and offshore building, saltwater resistant



mill finished

Load capacity :

Distance on center in mm	300
Payload in kN/m ²	Bearing distance in mm, Maximum
2	1100
4	900
5	800

Distance on center in mm	450
Payload in kN/m ²	Bearing distance in mm, Maximum
2	950
4	750
5	700

Distance on center in mm	400
Payload in kN/m ²	Bearing distance in mm, Maximum
2	1000
4	800
5	750

Distance on center in mm	500
Payload in kN/m ²	Bearing distance in mm, Maximum
2	900
4	750
5	700

Accessories:

Length connector aluminum 56 x 26 x 200mm
Bracket stainless steel 40 x 15 x 1,75mm

GS Götz Schmitt GmbH
An der Autobahn 62
28867 Oyten | Germany
www.gs-schmitt.com

Telefon: ++ 49 4202 888 9925
Telefax: ++ 49 4202 888 9926
E-Mail: info@gs-schmitt.com

aMbooo
Highland Bamboo only

Geschäftsführer: Götz. Schmitt
Steuer Nummer 481201102736
Amtsgericht Walsrode HRB 121551
USt - Nr. DE286136864

Bankverbindung:
Kreissparkasse Verden / BLZ 291 526 70
Konto.Nr. 12 51 64 31
IBAN: DE96 2915 2670 0012 5164 31
SWIFT-BIC: BRLA DE 21VER

US-Dollar-Bankverbindung:
Kreissparkasse Verden / BLZ 29152670
Konto.Nr. 2403082785
IBAN: DE22 2905 0000 2403 0827 85
SWIFT-BIC BRLA OE 22 (USD)